



REV	DESCRIPTION	DWN	DATE	APPROVEN
R1.0	First issue	Gavin	2025/02/24	JIM. KING



Specifications:

IMPEDANCE: 50 Ohms

Frequency range:0~3GHZ

Working voltage:335V rms @ sea level

Insulation resistance:1000 MOhms min

Temperature range:-20℃ TO +80℃

4	MCX Plug	RHT-617-0150	Brass, Gold Plating	1
3	Cable	CA-101-0696	RG174, Jacket:FEP Brown, OD:2.8±0.2mm	1
2	Heat shrink tubing		Black, L=20mm	2
1	BNC Plug	RHT-610-1117	Brass, Nickel Plating	1
NO	PART NAME	P/N	DESCRIPTION	QTY

-TOLERANCES- UNLESS OTHERWISE SPECIFIED	 Buy From Original Factory www.elecbee.com					
	 		PART DESCRIPTION: BNC MALE TO R/A MCX MALE FOR RG174 CABLE			
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 -120mm ± 0.30mm	Appd: JIM. KING		P/N: EB-101-0696			
	Check:		Date	Scale	Unit	Type Page
	Draw: Gavin		2025.02.24	Free	MM	Z 1/1

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.25mm
30 - 120mm ± 0.30mm